DELOCK®

we move the world

From STANDARD to EXOTIC

Card Reader
Curiosities

**91686**
USB 3.0 to CFast

91689
eSATAp to Compact Flash

91695
USB 3.0 to Compact Flash

91692
2,5 SATA to Compact Flash

61793
Express Card to CFast

FIRE WIRE B
91694
Card Reader FireWire B to Compact Flash

EXOTIC FACTOR

Card Reader

- More than **50** different Card Reader
- External- / internal- or PCMCIA version
- Multipanel with additional interfaces
- All in one Card Reader which can read and write up to 61 memory cards
- Special adapter for Card Reader
- Copy station and much more

'p' for Power

eSATAp

By media and notebook manufacturers
also called as

Power over eSATA
Combi connector eSATA/USB
Powered eSATA

*Notebook with **eSATAp** interface*

Available on
most new notebooks:
Super Speed eSATAp
3 Gb/s
interface

Enables the
connection of
USB
devices like
mouse, card reader
etc.

Enables the
connection of
eSATA
devices like
external HDD
etc.

Enables the
connection of
eSATAp
devices like
memory sticks, enclosure
etc.

No extra power supply
for eSATAp devices
required

Question and answer

Can i connect a standard USB male plug to a eSATAp female port?

Yes, you can still use the eSATAp interface for your USB devices, whereas the data transfer rate will be reduced according to your connected device. If you want to use the full SATA speed of up to 3 Gb/s you may connect an eSATA or eSATAp device.

I have an eSATAp port.
When do I require an extra power supply ?

1. You still need an extra power supply or USB power cable if you want to operate your old eSATA or 3.5 USB HDD on the eSATAp port.

2. You **do not need an extra power supply** if you use an eSATAp device (example above).

3. Exceptions are bigger HDD like 3.5 inch. You will need an extra power supply **OR** you can connect it to an **eSATApd** (pd = Dual Power) port. It provides 5 V and 12 V.

The following devices offer a 12 Volt eSATApd port:
61725 Slot bracket 2 x **eSATApd** 5 V/12 V
61797 Slot bracket **eSATApd** 1 x port 5 V/12 V
61824 Slot bracket **eSATApd** 5 V/12 V + USB 2.0
89233 PCI Express Card to 2 x **eSATApd** 5V/12V
89238 PCI Card 1 x **eSATApd** 5 V/12 V external,
         1 x SATA internal

Which eSATAp devices does Delock offer?

- **For connection of eSATAp to an eSATAp interface** – here are some examples:

42465	54229 54230	91676	91689
2.5 Enclosure for SATA HDD	Memory stick 16GB / 32GB	Card reader CFast	Card reader Compact Flash

Some other devices with optional eSATAp cables like mobile racks are available: www.delock.com

- **For upgrading the PC or notebook by an eSATAp interface** – here are some examples:

61776	61725	89238	91669
Adapter USB 3.0 to eSATAp	Slot bracket 2 x eSATAp	PCI Karte eSATAp + SATA	3.5 Multipanel with eSATAp port

EXOTIC FACTOR

WLAN + Bluetooth

95865
USB
Bluetooth
2.1+EDR 400-01 (V7)
1T/R

95894
mini PCIe
WLAN+Bluetooth
1T/R

95868
USB
WLAN
1T/R **5 V**
150 Mbps

95903
Mini PCI
WLAN
2T/R a 300 Mbps

95901
Mini PCIe/USB
WLAN
1T/R USB 2.0
150 Mbps

Accessory

95835
Module connecting cable 10cm
6 pin WLAN USB

95902
Mini PCIe
3,5G HSPA Modem
1T/R

95859
USB
WLAN
1T/R **3 V**
150 Mbps

Your options for installation

Special

Internal connection   **External connection**

to enclosure

95904
Mini PCIe
HD Video Decoder

95880
Mini PCIe
SATA 3 Gb/s internal

95825
Mini PCIe
Video Capture Card

95881
Mini PCIe
USB 3.0

95857
Mini PCIe
2 x Giga LAN

95882
Mini PCIe
1 x FireWire A
2 x FireWire B

95890
Mini PCIe
4 x RS-232

95867
Mini PCIe
1 x Giga LAN

95888
Mini PCIe
DVI (Intel®)

95891
Mini PCIe
SD / SDHC I/F

95879
Mini PCIe
56 K Modem

95889
Mini PCIe
LVDS 24 Bit Dual
(Intel®)

95892
Mini PCIe
4 - wire
Touch Controller

Over 40 Industry-modules on www.delock.com

2in1 USB 2.0 Nano memory stick + micro SD slot

- Internal memory
  Read: 10 MB/s
  Write: 6 MB/s
- Card Reader for micro SD, micro SDHC,
  micro SDXC memory cards
  Read: 20 MB/s
  Write: 15 MB/s
- Windows XP/Vista/7/7-64,
  Mac OS 10.5, OS 10.6, Linux
- Dimension: 21 x 16.2 x 9.8 mm (L/W/H)

54271	**1 GB**	54274	**8 GB**
54272	**2 GB**	54275	**16 GB**
54273	**4 GB**	54276	**32 GB**

Card optional

Cable USB 2.0 to Blu-ray / DVD / CD / drive sharing

- USB 2.0 A male to USB 2.0 A male
- Access to optical disc drives CD / DVD / Blu-ray
- Identification of ODD through allocation of a
  drive letter
- Chip: cFeon F80-100HCP
- LED indicator blue
- Cable length: ca. 1,1 m
- Plug & Play
- No driver installation required
- Windows 2000/XP/Vista/7/7-64, Mac, Linux

82764

PCI Express Card to 4 x internal SATA 3 Gb/s

- Marvell chipset
- 4 x internal SATA 3 Gb/s
- Data transfer rate up to 3 Gb/s
- PCI Express x4
- Compliant with PCI Express 1.0a
- Port: A+B are bootable
  C+D are not bootable
- Hot Plug
- Windows XP/Vista/7/7-64, Linux Kernel 2.6.35

89280

Low Profile

2.5 Drive SATA to Compact Flash Card

- Supports CF-Card type I
- 22 pin SATA data- and power connector
- SATA specification revision 1.0
- Supports CF cards with PIO, DMA and
  UDMA mode
- Bootable with CF cards in fixed disk mode
- Dimension (LxWxH): 100 x 70 x 7.9 mm
- Windows 2000/XP/Server-2003/Vista/7,
  Mac OS 10.x or higher, Linux

91697

PCI Express Card to USB 3.0

- VIA chipset
- 3 x external USB 3.0 type A
- 1 x internal USB 3.0 type A
- 1 x internal Molex 4 pin power connector
- Data transfer rate up to 5 Gb/s
- Downwards compatible to USB 2.0, USB 1.1
- PCI Express x1
- Supports PCI Express 2.0
- Windows XP/Vista/7/7-64, Linux ab 2.6

89281

Low Profile

Adapter Displayport male to DVI 24+5 female

- Displayport 20 pin male to DVI-I 24+5 female
- DVI-I 24+5 (VGA not wired) with screw nuts
- Displayport specification 1.1a
- Resolution up to 1920 x 1200 and HDTV
  up to 1080p
- Standby detection, standby enter into sleep
  mode automatically
- 1 x ferrite core
- Cable length ca. 12,5 cm without connector

61847

2.5 Enclosure SATA HDD to USB 3.0

- USB 3.0 A interface
- Suitable for 2.5 SATA HDD:
  HDD height up to 9,5 mm
  SATA HDD up to 6 Gb/s
  HDD up to 2 TB
- Data transfer rate up to 5 Gb/s
- Downwards compatible to USB 2.0
- Dimension (LxWxH): 128 x 75 x 14 mm
- Hot Plug, Plug & Play
- Windows XP/XP-64/Vista/Vista-64/7/7-64, Linux

42486

Adapter Displayport male to VGA 15 pin female

- Displayport 20 pin male to VGA 15 pin female
- Displayport specification 1.1a
- VGA port with screw nuts
- Supports VGA, SVGA, XGA, SXGA, UXGA and
  HDTV up to 1080p
- Standby detection, standby enter into sleep
  mode automatically
- 1 x ferrite core
- Cable length ca. 12,5 cm without connector

61848

5.25 Enclosure for SATA drive to USB 3.0

- Internal SATA 22 pin interface
- For 3.5 HDD or 5.25 SATA drive
- Data transfer rate up to 5 Gbps
- Supports DVD±RW, DVD-ROM, CD-RW,
  CD-ROM, Blu-Ray
- Suitable for all SATA drives up to 6 Gb/s
- Dimension (LxWxH): 260 x 170 x 53 mm
- Hot Swap, Plug & Play
- MAC OS 10.5, 10.6, Linux

42484

Adapter Displayport male to HDMI female

- Displayport 20 pin male to HDMI 19 pin female
- Displayport specification 1.1a
- High Speed HDMI
- Resolution up to 1920 x 1200 and HDTV
  up to 1080p
- Standby detection, standby enter into sleep
  mode automatically
- 1 x ferrite core
- Cable length ca. 12,5 cm without connector

61849

More detailed information about our products as well as a list of all compatible
memory cards for the Card Reader can be found on

www.delock.com